Dresser Atlas

COMPENSATED

Densilog

FILE NO.	
TIGHT HOLE !	COMPANY ATLANTIC INTERNATIONAL
	WELL VERNON DALTON NO. 1
	FIELD WILDCAT
	COUNTY ELKO STATE NEVADA
	LOCATION:
	SEC TWP RGE

Other Services: IEL, Diff Temp.

Permanent Datum Ground Level Elev.
Log Measured from Kelly Bushing, 10 Ft. Above Permanent Datum
Drilling Measured from " "

Elevations: KB 5621', DF 5620, GL 5611

Date	11-28-73			
Run No	TWO			
Depth—Driller	4205			
Depth—Logger	4187			
Bottom Logged Interval	4185			
Top Logged Interval	3690			
Casing—Driller	8 5/8 @ 320	@	@	@
Casing—Logger	318			
Bit Size	7 7/8			
Type Fluid in Hole	CHEM GEL			
Density and Viscosity	9.2 / 42			
pH and Fluid Loss	5.0 cc	cc	cc	cc
Source of Sample	Circulated			
Rm @ Meas. Temp.	4.4 @ 72 °F	@ °F	@ °F	@ °F
Rmf @ Meas. Temp.	4.1 @ 68 °F	1.18 @ 236 °F	@ °F	@ °F
Rmc @ Meas. Temp.	4.6 @ 72 °F	1.4 @ 236 °F	@ °F	@ °F
Source of Rmf and Rmc	M / M			
Rm @ BHT	1.34 @ 236 °F	@ °F	@ °F	@ °F
Time Since Circ.	3.5 HR.			
Max. Rec. Temp. Deg. F.	236 °F	°F	°F	°F
Equip. No. and Location	HL-6089 ROSVLT.			
Recorded By	MARTIN-WILCOX			
Witnessed By	M. SLAYNTER			

FIELD PRINT

FOLD HERE

Remarks:

Equipment Used: S.O. 41164; Tool No. 29227; Elec. No. 29227; Panel No. 26313

Equipment Data — Densilog: Run No. TWO; Tool Model No. 2208; Serial No. 29227; Diam. 3"; Computer Model No. 2254; Serial No. 26313; Source Model No. S3E20; Serial No. C-83

Gamma Ray: Run No. TWO; Tool Model No. 1305; Serial No. ; Diam. 3 5/8; Detect. Model No. 2604; Type SCINT; Length 6"; Dist. to Source 10"