Century Geophysical Corporation
Tulsa, Oklahoma

C-366-D

DATE	5-24-70
COMPANY	TENNECO OIL CO
BORE HOLE	#6 CORE HOLE
AREA	EASTERN GREAT BASIN
COUNTY	WHITE PINE
STATE	NEVADA
SECTION	32
TOWNSHIP	18 N
RANGE	58 E
LOG MEASURED FROM	GROUND LEVEL
HOLE NO.	
SEC / TWP. / RANGE	
AREA	
COUNTY	
STATE	
COMPANY	
DATE	
TOTAL FEET LOGGED	201 FT
T. D. DRILLED	920 Ft.
BIT SIZE	4 3/4 In.
CASING	
BORE HOLE FLUID	H_2O
DENSITY	
VISCOSITY	
RESISTIVITY	
OPERATOR	E. DEITER
UNIT NO.	7410
LOCATION	GRANTS N.M.
DRIVE	2.0 Hrs.
TIME IN	1700
STANDBY	Hrs.
TIME OUT	1800
LOGGING	1.0 Hrs.
TOTAL	3.0 Hrs.
ROUNDTRIP MILEAGE	78 Miles
CHARGEABLE STANDBY	— Hrs.

INITIAL RUN	
T. D. LOGGED	901 Ft.
GAMMA (FULL SCALE)	25 Cps.
TIME CONSTANT	4 Sec.
LOGGING SPEED	15 Ft./Min.

GAMMA RERUNS (Initial run offscale)

SCALE	T. C.	LOGGING SPEED	FROM	TO	TOTAL
Cps.	Sec.	Ft./Min.	Ft.	Ft.	
Cps.	Sec.	Ft./Min.	Ft.	Ft.	
Cps.	Sec.	Ft./Min.	Ft.	Ft.	

CALIBRATION

SOURCE NO.	5A
SOURCE VALUE	780 c/s
PROBE SIZE	H-213 1 3/8 In.
RES. (FULL SCALE)	50 ohms
S. P.	NONE Mv/In.

RELOG DEEPENED HOLE FROM 901 FT TO 700 FT

SELF POTENTIAL
− MV +

NATURAL GAMMA RAY
COUNTS PER SECOND

CALIPER

RESISTANCE
OHMS