Schlumberger — **DUAL LATEROLOG**

COMPANY	NORTHWEST EXPLORATION COMPANY
WELL	JAKES WASH #5A
FIELD	WILDCAT
COUNTY	WHITE PINE
STATE	NEVADA
LOCATION	1334' FSL & 1253' EWL
SEC	1
TWP	14N
RANGE	60E
Other Services	FDC-CNL-GR, BHC-GR, TAPING

Permanent Datum: GL ; Elev.: 6445
Log Measured From KB 12 Ft. Above Perm. Datum
Drilling Measured From KB
Elev.: KB 6457 D.F. ____ G.L 6445

Date	6/8/78			
Run No.	ONE			
Depth—Driller	4410			
Depth—Logger (Schl.)	4390			
Btm. Log Interval	4376			
Top Log Interval	1380			
Casing—Driller	9 5/8" @ 1372	@	@	@
Casing—Logger	1380			
Bit Size	8 3/4			
Type Fluid in Hole	FGM			
Dens. / Visc.	8.8 / 61			
pH / Fluid Loss	10.5 / 4 ml	ml	ml	ml
Source of Sample	FLOWLINE			
Rm @ Meas. Temp.	4.73 @ 57 °F	@ °F	@ °F	@ °F
Rmf @ Meas. Temp.	3.5 @ 57 °F	@ °F	@ °F	@ °F
Rmc @ Meas. Temp.	7.09 @ 57 °F	@ °F	@ °F	@ °F
Source: Rmf / Rmc	C / C			
Rm @ BHT	2.36 @ 114 °F	@ °F	@ °F	@ °F
Circulation Stopped	0230			
Logger on Bottom	0600			
Max. Rec. Temp.	114 °F	°F	°F	°F
Equip. / Location	7674 / VERNAL			
Recorded By	VALENTI			
Witnessed By Mr.	WITTER/FRENCH			

The well name, location and borehole reference data were furnished by the customer.

Run No. ONE; Service Order No. 40019; Fluid Level FULL; Salinity, PPM Cl. 100

SIMULTANEOUS DUAL LATEROLOG CALIBRATION CODING
1. MECHANICAL ZERO
2. RECORD SET (SP CALIBRATE)
3. TEST - 1 (1 ohm-m)
4. TEST - 2 (1000 ohm-m)
5. TOOL CAL (31.6 ohm-m)

CALIBRATION RECORD

COMPANY NORTHWEST EXPLORATION CO.
WELL JAKES WASH #5A
FIELD WILDCAT
COUNTY WHITE PINE STATE NEVADA
SCHL FR. 4376
SCHL TD. 4390
DRLR TD. 4410
Elev. KB 6457 DF GL 6445