Schlumberger

COMPENSATED NEUTRON-LITHO DENSITY

COMPANY TRUE OIL COMPANY

WELL SHIELDS FEDERAL #13-27

FIELD WILDCAT

COUNTY WHITE PINE STATE NEVADA

LOCATION 2250' FSL & 400' FWL

SEC 22 TWP 13N RANGE 61E

Other Services: TEMP, BHC, DLL

Permanent Datum: GL, Elev. 5929

Log Measured From KB 15.5 Ft. Above Perm. Datum

Drilling Measured From KB

Elev.: K.B. 5944, D.F. 5943, G.L. 5929

Date	1-6-86
Run No.	ONE
Depth – Driller	4256
Depth – Logger	4256
Btm. Log Interval	4254
Top Log Interval	2024
Casing – Driller	10-3/4 @ 2025
Casing – Logger	2024
Bit Size	9-7/8
Type Fluid in Hole	AIR
Rm @ BHT	@ 132 °F
Circulation Stopped	1-6 @ 0130
Logger on Bottom	1-6 @ 0930
Max. Rec. Temp.	132 °F
Equip. / Location	101 EVSTN
Recorded By	RICHTER
Witnessed By	HANSEN

REMARKS: BOWSPRING USED-LIMESTONE MATRIX MDEN=2.71 FROM 2454 TO 2024 FLUID IN HOLE IS FORMATION WATER WITH A RESISTIVITY OF 24.5 AT 54 DEGREES F.

RUN NO.	ONE
Service Order No.	444963
Program Tape No.	28.2

EQUIPMENT DATA

Module	418
Telemetry Cart.	212
Dens. Cart.	896
Dens. Skid	1836
Dens. Sonde	2728
Dens. Source	6806
Neut. Cart.	233
Neut. Source	1340
Neut. Calibrator	2619
GR Cart.	202
Eccentralizer	BOWSPRING