Schlumberger

WELL SEISMIC MONITOR LOG

COMPANY	ANADARKO PETROLEUM CORP.
WELL	COMBS CREEK FEDERAL #6-21
FIELD	WILDCAT
COUNTY	WHITE PINE STATE NEVADA
LOCATION	3700 FWL 1000 FNL
API SERIAL NO.	SECT. 6 TWP. 20N RANGE 62E

Other Services: DLL/MSFL, BHC, LDT/CNL, ML, NGT, FMS/SHDT

Permanent Datum	GL	Elev.	6306.0 F
Log Measured From	KB	15.0 F	above Perm. Datum
Drilling Measured From	KB		

Elev.: K.B. 6321.0 F; D.F. 6320.0 F; G.L. 6306.0 F

Date	12-MAY-1991	
Run No.	2	
Depth Driller	6435.0 F	
Depth Logger (Schl.)	6294.0 F	
Btm. Log Interval	6200.0 F	
Top Log Interval	1340.0 F	
Casing-Driller	13 3/8" @1319.0 F	
Casing-Logger	1319.0 F	
Bit Size	8 3/4"	
Type Fluid in Hole	LSND	
Dens. / Visc.	8.70 LB/G	41.0 S
pH / Fld. Loss	9.0	7.4 C3
Source of Sample	MUD TANK	
Rm @ Meas. Temp.	3.760 OHMM @ 66.0 DEGF	
Rmf @ Meas. Temp.	3.510 OHMM @ 66.0 DEGF	
Rmc @ Meas. Temp.	3.840 OHMM @ 66.0 DEGF	
Source: Rmf / Rmc	MEAS	CALC
Rm @ BHT	1.314 OHMM @ 203. DEGF	
Time: Circulation Ended	09:30 5/11	
Time: Logger on Bottom	15:30 5/12	
Max. Rec. Temp.	203. DEGF	
Equip. / Location	8305	EVANSTON
Recorded By	C. PRESMYK	
Witnessed By	J. HERSCH/B. WILEY	

The well name, location and borehole reference data were furnished by the customer.

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to Clause 4 of our General Terms and Conditions as set out in our current Price Schedule.

Run No.	2
Service Order No.	564271
Drilling Fluid Level	
Salinity	
Rmf @ BHT	1.220 OHMM @ 203. DEGF
Rmc @ BHT	1.308 OHMM @ 203. DEGF
Logging Speed	3000.0 F/HR
EQUIPMENT DATA	
Tool Number 1	TCM AB 1628
Tool Number 2	WSAM AB 744
Tool Number 3	WSAC AB 867
Tool Number 4	WSAA A 820
Tool Number 5	WSPC A
Tool Number 6	ONE LRS 315

REMARKS:

ONE LRS 315 VIBE USED

VIBE LOCATED 307' AT 130 DEG, ELEV=6306

SWEEP USED IS 10-82 HZ, 12 SECOND LINEAR UPSWEEP

TAPER=.25