ATLAS WIRELINE SERVICES
Western Atlas International

DIGITAL ARRAY ACOUSTIC GAMMA RAY (Slowness Presentation)

FILE NO.
API NO.
TIGHT HOLE

COMPANY ANSCHUTZ CORPORATION
WELL BUCK MOUNTAIN #36-1
FIELD WILDCAT
COUNTY WHITE PINE STATE NEVADA
LOCATION: 1815' FNL & 775' FEL SE/NE
SEC 36 TWP 21-N RGE 56-E

OTHER SERVICES: GR/ZDL/CN, GR/DIP/CBIL

PERMANENT DATUM GROUND LEVEL ELEVATION 7340 FT.
LOG MEASURED FROM K.B. 19 FT. ABOVE PERMANENT DATUM
DRILL. MEAS. FROM K.B.

ELEVATIONS: KB 7358, DF 7457, GL 7340

IN MAKING INTERPRETATIONS OF LOGS OUR EMPLOYEES WILL GIVE CUSTOMER THE BENEFIT OF THEIR BEST JUDGEMENT, BUT SINCE ALL INTERPRETATIONS ARE OPINIONS BASED ON INFERENCES FROM ELECTRICAL OR OTHER MEASUREMENTS, WE CANNOT, AND WE DO NOT GUARANTEE THE ACCURACY OR CORRECTNESS OF ANY INTERPRETATION. WE SHALL NOT BE LIABLE OR RESPONSIBLE FOR ANY LOSS, COST, DAMAGES, OR EXPENSES WHATSOEVER INCURRED OR SUSTAINED BY THE CUSTOMER RESULTING FROM ANY INTERPRETATION MADE BY ANY OF OUR EMPLOYEES.

DATE	08/17/92			
RUN	ONE			
SERVICE ORDER	115698			
DEPTH DRILLER	78 E			
DEPTH LOGGER	78 4			
BOTTOM LOGGED INTERVAL	7735			
TOP LOGGED INTERVAL	313			
CASING - DRILLER	13 3/8 @ 875	@	@	@
CASING LOGGER	826			
BIT SIZE	12 1/4			
TYPE FLUID IN HOLE	L S N D			
DENSITY / VISCOSITY	8.6 / 53			
PH / FLUID LOSS	8 / 6 8			
SOURCE OF SAMPLE	FLOW			
RM AT MEAS. TEMP.	2.74 @ 88	@	@	@
RMF AT MEAS. TEMP.	2.15 @ 80	@	@	@
RMC AT MEAS. TEMP.	3.04 @ 78	@	@	@
SOURCE OF RMF / RMC	MEAS / MEAS			
RM AT BHT	.92 @ 128	@	@	@
TIME SINCE CIRCULATION	8 HRS.			
MAX. REC. TEMP. DEG F	78			
EQUIP. NO. / LOCATION	HL 5539 / ROCK SPRNG			
RECORDED BY	TRIBBLE			
WITNESSED BY	MR. MCCOY			

REMARKS
USED MATRIX DELTA-T OF 47.6 MICS/FT IN COMPUTING ACOUSTIC POROSITY.

EQUIPMENT DATA

RUN	TRIP	TOOL	SERIAL NO.	SERIES NO.	POSITION