Schlumberger

SAT CHECK SHOT SURVEY

COMPANY	ANADARKO PETROLEUM CORPORATION
WELL	OVERLAND PASS FEDERAL #29-14
FIELD	WILDCAT
COUNTY	WHITE PINE
STATE	NEVADA

CONFIDENTIAL

LOCATION	2800' FNL & 900' FEL			Other Services: DLL/MSFL, BHC SONIC, NGT, LDT, CNL, FMS
API SERIAL NO.	SECT.	TWP.	RANGE	
N/A	29	25N	56E	

Permanent Datum	Ground Level	Elev.	6102.9 F	Elev.: K.B. 6119.8 F
Log Measured From	KB	16.9 F	above Perm. Datum	D.F. 6118.8 F
Drilling Measured From	KB			G.L. 6102.9 F

Date	06-DEC-1993		
Run No.	ONE		
Depth Driller	2530.0 F		
Depth Logger (Schl.)	2527.0 F		
Btm. Log Interval	2510.0 F		
Top Log Interval	200.0 F		
Casing-Driller	9 5/8" @ 1583.0 F	@	@
Casing-Logger	1578.0 F		
Bit Size	8 3/4" @ 2530.0 F	@	@
Type Fluid in Hole	LSND		
Dens. / Visc.	8.60 LB/G	38.0 S	
pH / Fld. Loss	8.5	8.2 C3	
Source of Sample	MUD PIT		
Rm @ Meas. Temp.	9.630 OHMM @ 62.0 DEGF	@	
Rmf @ Meas. Temp.	9.050 OHMM @ 62.0 DEGF	@	
Rmc @ Meas. Temp.	9.510 OHMM @ 62.0 DEGF	@	
Source: Rmf / Rmc	MEASURED	CALCULATED	
Rm @ BHT	4.886 OHMM @ 129. DEGF	@	
TIME: Circulation Ended	06:30 06-DEC-1993		
TIME: Logger on Bottom	06:45 DEC-06-93		
Max. Rec. Temp.	129. DEGF		
Equip. / Location	8305	Evanston WY	
Recorded By	D. REINHEIMER		
Witnessed By	B. WILEY, D. HAZLETT		

The well name, location and borehole reference data were furnished by the customer.

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretations made by any of our officers, agents or employees. These interpretations are also subject to Clause 4 of our General Terms and Conditions as set out in our current Price Schedule.

Run No.	ONE
Service Order No.	625106
Drilling Fluid Level	0.0 F
Salinity	200.0 PPM
Rmf @ BHT	4.592 OHMM @ 129 DEGF
Rmc @ BHT	4.825 OHMM @ 129 DEGF
Logging Speed	2200.0 F/HR
EQUIPMENT DATA	
Tool Number 1	WSAS A 420
Tool Number 2	WSAM-AB 744
Tool Number 3	TCM-AB 473
Tool Number 4	WSI-A 787
Tool Number 5	ADV I ESG
Tool Number 6	
Tool Number 7	
Tool Number 8	
Tool Number 9	
Tool Number 10	
Tool Number 11	
Tool Number 12	

REMARKS:

SINGLE VIBRATOR SOURCE USED

SOURCE OFFSET 154 FT / AZIMUTH 72 DEG TRUE

SOURCE ELEVATION 6102.9 FT