WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 637
Rec. 9/11 1948
Well No.
Permit No.
Do not fill in

Basin #110A 48

Owner U.S.J.S. Driller J B Reynolds

Address Shurz Nevada Address Fallon Nevada Lic. No. 28

Location of well: ¼ ¼ Sec. 24, T. 13 N/S, R. 29 E, in MINERAL County

or This well is located at Double spring. SIX Miles. EAST OF SHURZ

Water will be used for cattle Total depth of well 102

Size of drilled hole 7 1/8 Weight of casing per linear foot 28

Thickness of casing 5/16" Temp. of water cold

Diameter and length of casing 7 1/8" X 50'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well Date of completion of well

Type of well rig Star 11 - cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	16	16	clay
16	33	17	gravel
33	37	4	blue clay
37	52	15	grey clay
52	76	14	hard pan
76	102	26	gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 76 to 102 ft.

Other aquifers 16 - 33

artesian water (bad)

First water at 16 feet.

Casing perforated

from to ft.

no perforation

Size of perforations

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
7 1/8	0	50	50	are welded joints

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. B. Reynolds
Well Driller

By .....

License No. 26

Dated Sept 10, 1948

(Not to be filled in by Driller)